



SE NOR TECH CO., LTD.

No.165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan
 Tel: +886-2-26950405 Fax: +886-2-26952745
<http://www.senortech.com> E-mail: sales@senortech.com

Standalone Thermal Printer

GTP-150



2012/11/06

Specifications							
Printing Technology		Direct Line Thermal Method					
Print Resolution		8 dot/mm (0.125mm/dot) 203dpi					
Printing Speed		Maximum 220mm/s (Monochrome only)					
Paper Feed-out Direction		Top feed out					
Cutter Method		Partial cut					
Installation Direction		Two ways (Horizontal / Vertical)					
Paper	Paper width	80mm, 58mm					
	Out Diameter of Roll Paper	Ø83mm Maximum					
	Paper Thickness	64µm - 85µm					
	58mm width paper	48mm (384dots) or 52.5mm (420dots)					
	80mm width paper	64mm (512dots) or 72mm (576dots)					
Font size & Column			203dpi (Normal Mode)			Approx. 180dpi (Extended Mode)	
			Font A (Column)	Font B (Column)	Font C (Column)	Font A (Column)	Font B (Column)
	Paper width 58mm	Body Face	12x24 (32 or 35)	10x24 (38 or 342)	8x16 (48 or 52)	12x24 (32 or 35)	10x24 (38 or 342)
				9x24 (42 or 46)			9x24 (42 or 46)
		Letter Face	11x22 (32 or 35)	9x17 (38 or 42)	8x13 (48 or 52)	12x24(32 or 35)	9x22 (38 or 42)
				9x17 (42 or 46)			9x22 (42 or 46)
	Paper width 80mm	Body Face	12x24 (42 or 48)	10x24 (51 or 57)	8x16 (64 or 72)	12x24 (42 or 48)	10x24 (51 or 57)
				9x24 (56 or 64)			9x24 (56 or 64)
		Letter Face	11x22 (42 or 48)	9x17 (51 or 57)	8x13 (64 or 72)	12x24 (42 or 48)	9x22 (51 or 57)
				9x17 (56 or 64)			9x22 (56 or 64)
	Character Sets		ANK(95 char.), International Character(48 char.), Enlarged Graphics(128 char. x 20 pages), Download Character(95 char.)				



SEVOR TECH CO., LTD.

No.165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan
 Tel: +886-2-26950405 Fax: +886-2-26952745
<http://www.sevortech.com> E-mail: sales@sevortech.com

Standalone Thermal Printer

GTP-150



2012/11/06

Specifications				
Barcode	Barcode		UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), CODE39, ITF, CODEBAR(NW-7), CODE93, CODE128	
	Two dimensional code		QR code	
Receive Buffer			Max. 4KB	
Logo Store Memory			Max. 576KB	
Paper Near End & Paper End			Available	
Internal Buzzer			Available to notice errors and printer status	
Interface	Dual (RS232C+USB)		RS232C Serial + USB (2.0 Full speed)	
Software Interface			ESC/POS emulation	
Drawer Interface			2 Drawers Controllable	
Software	Printer Driver	Windows	Windows driver	Windows® Server 2008 R2, Windows® Server 2008, Windows® 2003, Windows® 7, Windows® Vista, Windows® XP, POSReady 7, POSReady 2009, WEPOS
			OPOS driver	
			JavaPOS driver	
		Linux	JavaPOS driver	Linux
	Printer Utility		Software to set the printer's setup items	
Reliability	MCBF		60 million Lines	
	Print Head		100km	
	Cutter Life		1.5 million time of partial cut (Recommended Normal paper use)	
Power Requirements			DC Input: +24VDC±10% AC Input: 100-240V, 50/60Hz, Single Phase	
Power Consumption			During standby Dual Interface:3W or less Average during operating 38W or less, Maximum 150W or less	
Ambient Temperature			Operation guarantee:0℃ to 40℃ Print quality guarantee: :5℃ to 35℃	
Relative Humidity			Operation guarantee:10%RH to 95%RH Print quality guarantee:10%RH to 85%RH	
Dimensions			144(W)x184(D)x120(H)mm, 5.7(W)x7.2(D)x4.7(H) inch	
Weight(without the packing box)			1.2 kg	
Cover Color			Black or White	
Option			Splash-proof cover, Wall hanging bracket	

※ **NOTE:** The product information and specifications are subject to change without notice.